



60-J Diesel Telescopic Boom

**Full-Featured,
Rugged, Simple,
Reliable**

- 66 ft. (20 m) Working Height with Standard 6 ft. (1.8 m) Jib for 135° Jib Range of Motion
- Full-time Hydrostatic 4WD with Oscillating Axle and 45% Gradeability
- Standard 8 ft. (2.4 m) Platform Includes 3-Sided Entry with Swing Gate
- Award-Winning Proactive Platform Safety System (PPSS) Available
- Continuous 360° Turntable Rotation



Transport 2 per Truck - Only 17,900 lbs. (8119 kg) Each

Standard Features

Work Area

90" (2.3 m) Work Platform
 3-Sided Entry with Swing Gate
 500 lb. (227 kg) Platform Capacity
 180° Platform Rotation
 135° Jib Range of Motion
 Power to Platform

Performance

360° Continuous Turntable Rotation
 4WD Closed Loop Positive Traction Drive System
 45% Gradeability
 Oscillating Axle
 Self-Leveling Platform
 Low Engine RPM Elevated Operation
 Two-Speed Drive Motors
 66 ft. (20.1 m) Working Height
 Full Drive Height

Control System

Triple Joystick Interface
 Fully Proportional Multi-Function Controls

Power

44 HP Kubota Tier 4 Final

Safety

Emergency Shut-Off on Platform & Chassis	Tilt Alarm and Horn
Auxiliary Power Unit	Four Wheel SAHR Braking System
Multi-Axis Tilt Sensor	Automotive Horn
	Engine Shut Down Protection

Other Features

Hour Meter
 Machine Tie-Downs and Lifting Lugs
 Lanyard Attachments
 Standard Solid RT Tires
 On-Board Diagnostics

Optional Features

Flashing Beacon (Continuous)	Glazier Package
Platform Control Box Cover	Cold Start Package
Platform Work Lights	CSA Compliant Options
All Motion Alarm	Proactive Platform Safety System® (PPSS)
7.5 kW Welder Ready Generator	Second Year Extended Warranty
3.5 kW AC Generator	



MEC Aerial Work Platforms

Tel: 559.842.1500 | 1401 S. Madera Avenue, Kerman, CA 93630 | USA
 Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Fax: 559.842.1520
 Email: info@MECawp.com | www.MECawp.com

MEC® and Proactive Platform Safety System® are registered trademarks of California Manufacturing & Engineering Co., LLC. 97019 DTD 1021

60-J Diesel	
Heights	Diesel
Working Height*	66 ft.*/20.1 m*
Maximum Platform Height	60 ft./18.3 m
Maximum Drive Height	60 ft./18.3 m
Maximum Outreach	42 ft. 8 in./13 m
Turntable Swing	Continuous
Jib Range of Motion	135°
Platform Rotation	180° (90° each side)
Platform Size/Capacity	
Standard Platform Capacity	500 lbs./227 kg
Personnel Capacity	2 Persons
Platform Width	90 in./2.3 m
Platform Depth	40 in./1 m
Platform Entry	1 End Swing Gate, 2 Slide Bars
Machine Dimensions	
Length – Stowed (Overall)	30 ft. 6 in./9.3 m
Width	96 in./2.4 m
Overall Height	100 in./2.5 m
Tailswing	47 in./1.2 m
Weight**	17,900 lbs.**/8119 kg**
Working Conditions	
Drive	4 Wheel Drive
Gradeability	45% (24°)
Ground Clearance	12 in./0.3 m
Breakover Angle	22°
Axle Oscillation	20° (10° each direction)
Tires	Foam-Filled Std., Non-Marking Optional
Power	
Power Source	44 HP Kubota Tier 4 Final Turbo Diesel
Fuel Capacity/Power Supply	32 gal/121 L
Hydraulic Oil Capacity	40 gal/151 L
Movement	
Inside Turning Radius	6 ft. 6 in./2 m
Drive Speed	4.0 mph/6.4 km/h
Boom Lift Speed	55 sec.
Boom Extend Speed	25 sec.
Jib Lift Speed	20 sec.

*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.
 **Weight may vary with certain options or configurations.

Important - MEC lifts must be on a hard level surface while elevated. **Warranty** - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.20 and CSA B354.6.

Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by: