



American Pneumatic Tools

MODEL 155 ROCK DRILL

DRY DRILLING MODELS

PART # 5229 (7/8" HEX x 3-1/4")

PART # 5231 (7/8" HEX x 4-1/4")

PART # 5233 (1" HEX x 4-1/4")

WET DRILLING MODELS

PART # 5230 (7/8" HEX x 3-1/4")

PART # 5232 (7/8" HEX x 4-1/4")

PART # 5234 (1" HEX x 4-1/4")



The APT Model 155 Rock Drill is a tough, 60 lb class Rock Drill. This tool can be used in general construction as well as in utility work and plant maintenance. It is designed for drilling through granite, hard faced rock, quarry drilling, and drilling secondary holes for blasting. This tool can also be used with dowel hole drilling machines. Adaptable to wet drilling applications by attaching the APT valve, wet tube and swivel assembly.

SPECIFICATIONS

| Part # | 5229 | 5230 | 5231 | 5232 | 5233 | 5234 |
|------------------------|---------------|------|---------------|------|-------------|------|
| Type | Dry | Wet | Dry | Wet | Dry | Wet |
| Hex Chuck Size | 7/8" x 3-1/4" | | 7/8" x 4-1/4" | | 1" x 4-1/4" | |
| Bore Diameter (inches) | 2-5/8" | | | | | |
| Stroke (inches) | 3" | | | | | |
| Blows per Minute | 2100 | | | | | |
| CFM @ 90 psi | 110 - 120 | | | | | |
| Weight (lbs) | 61 | | | | | |
| Length (inches) | 22-3/8" | | | | | |
| Air Inlet Size | 3/4" MALE NPT | | | | | |

FEATURES

- 3 drilling speeds
- Built-in automatic oiler
- Replaceable piston stem bearing
- Available in wet or dry models
- Counter clockwise rotation
- Rubber handle grips

For assistance in any sales, technical, maintenance or repair questions, please call APT @

Phone: (800) 532-7402 or (714) 285-2828 • Fax: (800) 715-6502 or (714) 285-2829

1000 S. Grand Ave, Santa Ana, CA 92705

Website: www.apr-tools.com • e-mail: info@apr-tools.com

TDS-1035 Rev B

© 2017 AMERICAN PNEUMATIC TOOLS a business unit within: Construction Equipment North America LLC.