

Micro 19

Electric Scissor Lift

- Compact Size without Compromising Generous Work Area
- Fits on Most Elevators With Shortest Overall Length and Low GVW (Gross Vehicle Weight)
- 24 in. (60 cm) Roll-out Deck Extension with Incremental Lock Positions
- Direct Electric Drive for Extended Duty Cycle, Smoother Control and Fewer Leak Points
- 2-person Platform with 500 lb. (226 kg) Capacity
- Fully Proportional Lift and Drive Controls



Standard Features

Work Area

Roll-Out Deck Extension with Incremental Locking Positions Standard Swing Gate Lanyard Attachments 110v Power to Platform

Performance

Direct Electric Drive Fully Proportional Drive and Lift Controls Up To 25% Gradeability

Power

24v 115Ah AGM DC Electric Power (Maintenance-Free Batteries)
Battery Charge Indicator
Single 110v Receptacle at Chassis for Common Plug Connection for Battery
Charger and Power to Platform

Serviceability

Lubrication-Free Scissor Bearings
Easy Maintenance Access to Mechanical and Electrical Components in a
Slide-Out Tray

Logically Grouped Components and Numbered Wiring for Easy Reference

Safety

Lift Control Orientation Designed to Mitigate Overhead Entrapment Dedicated Compartments Protect Electrical and Hydraulic Components Emergency Shut-Off at Platform and Lower Controls

Other Features

Leak Containment System® (LCS)
Removable Upper Controls
Voltage-Compensating Fully
Automatic Battery Charger
Hour Meter

Optional Features900W Inverter
Tool Tray

Pipe Rack Cold Weather Package Non-Skid Metal Deck Construction Descent Alarm Drive Speed Interlock Scissor Maintenance Lock Multi-Axis Tilt Sensor Multiple Disc Brakes Automatic Parking Brake

Machine Tie Downs
Non-Marking Tires
All Motion Alarm
Fork Lift Pockets
Flashing Beacon (Continuous)

Proactive Platform Safety System® (PPSS) Anti-Fatigue Mat Second Year Extended Warranty



MEC Aerial Work Platforms

Tel: 559.842.1500 | 1401 S. Madera Avenue, Kerman, CA 93630 | USA Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Fax: 559.842.1520 Email: info@MECawp.com | www.MECawp.com

MEC®, Micro 19®, Proactive Platform Safety System® and Leak Containment System® are registered trademarks of California Manufacturing & Engineering Co., LLC.
Leak Containment System® is Patent #11,112,060 94542 DTD 0224

Micro 19	U.S.	Metric
Heights		
Indoor Working Height*	24.4 ft.*	7.6 m*
Outdoor Working Height*	21 ft.*	6.6 m*
Indoor Platform Height	18.4 ft.	5.6 m
Outdoor Platform Height	15 ft.	4.6 m
Stowed Height (Top Guardrail)	79 in.	201 cm
Stowed Height (Platform Floor)	39 in.	99 cm
Guardrail Height	39 in.	99 cm
Toeboard Height	6 in.	15 cm
Ground Clearance (Stowed)	2.5 in.	6.4 cm
Ground Clearance (Elevated)	0.6 in.	1.5 cm
Dimensions		
Length-Stowed (Overall)	60 in.	152 cm
Length-Stowed (Ladder Removed)	54 in.	137 cm
Chassis Width	32 in.	81 cm
Platform Length (Extended)	78 in.	198 cm
Platform Length (Retracted)	54 in.	137 cm
Roll-Out Deck Length	24 in.	61 cm
Platform Width	27.5 in.	70 cm
Wheelbase	45 in.	114 cm
Total Lift Capacity	500 lbs.	227 kg
Personnel Capacity	2 (Indoors); 1 (Outdoors)	
Roll-Out Deck Capacity	250 lbs.	113 kg
Speed		
Raise/Lower Speed	26 s	20 s
Drive Speed (Stowed)	2.5 mph	4.0 km/h
Drive Speed (Elevated)	0.5 mph	0.8 km/h
Performance		
Gradeability	25%	25%
Turning Radius (inside)	18 in.	46 cm
Weight**	2,750 lbs.**	1,250 kg**
Power Source	24 v DC, 115Ah AGM Battery Pack	
Controls	Proportional Drive & Lift Controls	
Tires	9 in. x 4 in.	23 cm x 10 cm

*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.
**Weight may vary with certain options or configurations.

Important - MEC scissor lifts must be on a hard level surface while elevated.

Warranty - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.20 and CSA B354.6.

Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by: